

EXCEL PRO

All polyester rope, ideal for most applications on a dinghy. The twisted long lay core provides a low stretch option for halyards. The hard wearing brightly coloured cover is ideal for sheets in larger diameters and control lines when using small diameters.


APPLICATIONS	Halyards, Sheets, Control Lines, Kickers, Backstays, Out/Downh				
MATERIAL					
CORE:	Manufactured from high tenacity Polyester				
	Unaffected by water				
	Low creep				
	Zero shrinkage				
	Low water absorption				
COVER:	Manufactured from high tenacity Polyester				
	Good UV resistance				
	Good abrasion and heat resistance				
CONSTRUCTION					
TWISTED FIBRE CONSTRUCTION:	Improved abrasion resistance				
TWISTED CORE CONSTRUCTION:	Optimised pitch to yarn twist - improves strength and longevity				
	Firmer rounder rope, aids handling				
	Flexible product and easily handled				
16 PLAIT COVER CONSTRUCTION:	Protects load bearing core from dirt and abrasion				
16 PLAIT COVER CONSTRUCTION:					

PROPERTIES	
PROPERTIES	
RELATIVE DENSITY:	1.38 Exact figure varies with diameter
CHEMICAL RESISTANCE:	Excellent resistance to most chemicals
	(additional information available on request)
UV RESISTANCE:	Good
MELTING POINT:	260°C
CRITICAL TEMPERATURE:	N/A
TERMINATIONS	
SPLICED EYE TERMINATION:	N/A

ELONGATION

Typical working elongation (for a bedded in a rope):

@ 10% of break load: 1.7% @ 20% of break load: 2.8% To break: 13.0%



PERFORMANCE

DIAMETER	CIRCUMFERENCE	MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN
2	3/32	2.7	0.18	110	242	1.1	99	218	1.0
3	1/8	6	0.40	202	444	2.0	182	400	1.8
4	5/32	10.7	0.72	377	829	3.7	339	746	3.3
5	3/16	21.5	1.44	702	1544	6.9	632	1390	6.2
6	7/32	26.8	1.80	986	2169	9.7	887	1952	8.7

Marlow Ropes Ltd Ropemaker Park Hailsham

East Sussex, BN27 3GU England

Marlow Ropes, Inc. Cordage Business Park Plymouth MA 02360 USA

www.marlowropes.com UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com



Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.