

NEW Series

THETIS 7003

CHAIN COUNTER



Radio Control Chain counter THETIS 7003

Without cable ties, plug or panels and with load always perfect by rechargeable battery, the radio chain counter **THETIS 7003** gives finally all the **freedom of manoeuvres** and the **comfort of reading** in the anchoring operations.

Reinforced covers & buttons.

- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Switch on button / Key tones adjustment
- ✓ High vision LCD display / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection
- ✓ USB cable and charger included
- ✓ Cradle included

Code	73633
Command transmission	Remote
Number of buttons	3 (Transmitter)
Voltage	12 - 24V _{dc} (Receiver)
Operative temperature	-10 : +60
IP protection rated*	67 (Transmitter)**
Max contacts amperage (A)	2 (Receiver)
Weight (gr)	480
Dimension (mm)	154x59x38 (Transmitter)

**Excluding cable connection zone

THETIS 5003

CHAIN COUNTER



Hand Held Remote Control Chain counter THETIS 5003

This remote chain counter model **THETIS 5003** has been specifically designed to give the **full control in anchoring**. It's a reliable and practical instrument, technologically advanced, specifically design for use in marine environments. The external casing, rated with **IP66** and supplied with **waterproof plug** and **socket rated IP67**. The extending flexible cable (approximately 4 metres) gives the **maximum freedom** on board during anchoring manoeuvring. Provided with an evolved microprocessor that offers a series of advantages for **full control of the anchoring**.

Reinforced covers & buttons.

- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Switch on button / Key tones adjustment
- ✓ High vision LCD display / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection
- ✓ Cradle included

Code	73632
Command transmission	Wire
Number of buttons	3
Voltage	12 - 24V _{dc}
Operative temperature	-10 : +60
IP protection rated*	67
Max contacts amperage (A)	2
Weight (gr)	710
Dimension (mm)	154x59x38

*Excluding cable connection zone (IP68: plug & socket)

NEW Series

THETIS 1002

HAND HELD CONTROL



Cradle

Hand Held Control THETIS 1002

This hand held remote control model **THETIS 1002** has an **elegant and functional design**. The soft rubber case, which covers sideways the remote control, **allows a safe and handy taking under any condition**.

This hand held remote control is rated with **IP66** and supplied with **waterproof plug** and **socket rated IP67**. The extending flexible cable (approximately 4 metres) gives the **maximum freedom** on board during anchoring manoeuvring.

Reinforced covers & buttons.

- ✓ Inversion polarity protection
- ✓ Parallel connection
- ✓ 2 buttons (up-down)
- ✓ Cradle included

Code	73631
Command transmission	Wire
Number of buttons	2
Voltage	12 - 24V _{dc}
Operative temperature	-10 : +60
IP protection rated	67
Max contacts amperage (A)	2
Weight (gr)	580
Dimension (mm)	154x59x38

IRIS II

CHAIN COUNTER



Panel Chain counter IRIS II

This fly bridge chain counter **IRIS II** is technologically advanced instrument with an **elegant and ergonomic design** makes it suitable for all type of boat cockpits.

IRIS II is supplied with an evolved microprocessor, with different operations **allowing an optimum anchoring**.

New larger display.

- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Switch on button / Key tones adjustment
- ✓ High vision LCD display 3,3" / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection

Code	600017
Command transmission	Wire
Number of buttons	3
Voltage	12 - 24V _{dc}
Operative temperature	-10 : +60
IP protection rated*	67
Max contacts amperage (A)	2
Weight (gr)	500
Dimension (mm)	110x105x15**

* When installed **Recessed option