

Marlow[®] DATASHEET

EXCEL CONTROL

The ultimate continuous control line for dinghies. Easy to splice continuous loops with no diameter change. Technora/Polyester cover provides strength, grip and abrasion resistance.



APPLICATIONS

Dinghy control lines

MATERIAL

CORE:

Manufactured from Polypropylene
Very light weight

COVER:

Low water absorption
Manufactured from alternating Technora & Polyester
Good UV resistance
Excellent abrasion and heat resistance

CONSTRUCTION

TWISTED FIBRE CONSTRUCTION:

Improved abrasion resistance

8 STRAND BRAIDED

CORE CONSTRUCTION:

Optimised pitch to yarn twist - improves strength & longevity
Firmer rounder rope, aids handling
Easy to splice
Flexible product and easily handled
Torque balanced

16 PLAIT COVER CONSTRUCTION:

Protects load bearing core from dirt and abrasion
Round and firm construction

PROPERTIES

RELATIVE DENSITY:

1.2 Exact figure varies with diameter

CHEMICAL RESISTANCE:

Excellent resistance to most chemicals
(additional information available on request)

UV RESISTANCE:

Good

MELTING POINT:

240°C

CRITICAL TEMPERATURE:

140°C (exposure to temperatures over this will result in permanent strength loss)

TERMINATIONS

SPliced EYE TERMINATION:


Splicing instructions available online - www.marlowropes.com

ELONGATION

Typical working elongation:

@ 10% of break load: 4.40%

@ 20% of break load: 7.60%



PERFORMANCE

DIAMETER		CIRCUMFERENCE		MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN		
4	5/32	10.2	0.68	477.8	1051	4.7	460	1013	4.5		
5	3/16	15.9	1.07	765.2	1683	7.5	755.7	1663	7.4		

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.

Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

MA-DA-044 | ISSUE NO.2



Certification Number 315

ISO 9001