



ANKERPLEX
KEEPING THE POSITION

SIZE GUIDE ACCORDING TO CONDITIONS AND LENGTH

MODEL	MATERIAL	WEIGHT (Kg)	SURFACE (MM)	DINGHY KAYAK	5M 16'	6M 20'	7M 23'	8M 26'	9M 30'	10M 33'	11M 36'	12M 39'	13M 42'	14M 46'	15M 50'
AKP1ST	STAINLESS STEEL	1,3	16600	●●●	●										
AKP4ST	STAINLESS STEEL	4,4	35000		●●●	●●									
AKP4AL	ALUMINIUM	1,5	35000		●●●	●●									
AKP6ST	STAINLESS STEEL	6,9	43200			●●●	●●●	●●							
AKP6AL	ALUMINIUM	2,3	43200		XXX	●●●	●●●	●●							
AKP9ST	STAINLESS STEEL	9,9	62300					●●●	●●●	●●					
AKP9AL	ALUMINIUM	4,0	62300			XXX	XXX	●●●	●●●	●●					
AKP14ST	STAINLESS STEEL	14,4	75300							●●●	●●●	●●			
AKP14AL	ALUMINIUM	6,1	75300					XXX	XXX	●●●	●●●	●●			
AKP17ST	STAINLESS STEEL	17,2	89700									●●●	●●●	●●	
AKP17AL	ALUMINIUM	7,2	89700							XXX	XXX	●●●	●●●	●●	
AKP23ST	STAINLESS STEEL	23,8	98500											●●●	●●
AKP23AL	ALUMINIUM	10,6	98500									XXX	XXX	●●●	●●

●
●●
●●●
XXX

ENOUGH SIZE IN GOOD WEATHER CONDITIONS (DAY)

RIGHT SIZE FOR NORMAL CONDITIONS

RECOMMENDED SIZE - GENERAL USE IN ALL TYPES OF CONDITIONS

RECOMMENDED SIZE AS A LIGHT RESERVE ANCHOR (KEDGE)



AS A STORM ANCHOR IT IS SUGGESTED THE SIZE HIGHER THAN THE RECOMMENDED

