


# Marlow DATASHEET®

## D2 CLUB

**NEW COLOURWAYS AND LIGHTER WEIGHT**

D2 Club has been developed to provide an upgrade to polyester sheets and halyards offering the benefit of reduced weight and reduced elongation thanks to the light weight Dyneema® SK75 blended core. Due to the ropes equivalent strength and diameter to typical polyester braids, it can be simply substituted without the complexity and expense of having to modify or change deck equipment like clutches and winches. The coated core provides extra durability and ease for splicing.



<b>CORE MATERIAL:</b>	Dyneema® SK75 and Polypropelene coated core (ArmourCoat)
<b>COVER MATERIAL:</b>	Polyester
<b>TESTING METHOD:</b>	Apply check load according to BS EN ISO 2307 Measure sample length and weigh G/M according to BS EN ISO 2307 Measure rope pitch according to BS EN ISO 2307 Break in tensile testing machine (wedge grips)
<b>CONSTRUCTION</b>	
<b>CORE:</b>	12 strand
<b>COVER:</b>	16 plait
<b>COLOURS:</b>	blue, green, red and black
<b>LENGTHS:</b>	200m
<b>SPLICEABILITY:</b>	Terminate with a covered eye splice or uncoated eye splice. Can also be easily tapered.

**N.B. KNOTS WILL SIGNIFICANTLY REDUCE THE STRENGTH OF ANY ROPE. THIS PRODUCT WILL TYPICALLY RETAIN APPROXIMATELY 40% OF ITS STRENGTH IF TERMINATED WITH A KNOT. THE EXACT FIGURE WILL DEPEND ON THE TYPE OF KNOT USED AND OTHER FACTORS.**

DIAMETER		MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN
8	5/16	40.0	2.68	2260	2980	22.2	2034	4480	20.0
10	13/32	64.3	4.31	3820	8420	37.5	3440	7579	33.7
11	5/16	75.3	5.05	4240	9360	41.6	3820	8420	37.5
12	15/32	86.4	5.79	4790	10600	47.0	4311	9500	42.3
14	3/8	112.0	7.53	6370	14000	62.5	5733	12600	56.2

Marlow Ropes Ltd  
Ropemaker Park  
Hailsham  
East Sussex, BN27 3GU  
England

Marlow Ropes, Inc.  
Cordage Business Park  
Plymouth  
MA 02360  
USA

www.marlowropes.com  
UK: +44 (0) 1323 444 444  
sales@marlowropes.com  
US: +1 508 830 444  
salesusa@marlowropes.com

### Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.  
Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.  
Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.  
Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.  
MA-DA-019 | ISSUE NO.2



Certification Number 315

ISO 9001