


EXCEL PRO LEISURE MARINE

All polyester rope, ideal for most applications on a dinghy. The twisted long lay core provides a low stretch option for halyards. The hard wearing brightly coloured cover is ideal for sheets in larger diameters and control lines when using small diameters.



APPLICATIONS

MATERIAL CORE:

COVER:

CONSTRUCTION
TWISTED FIBRE CONSTRUCTION:
TWISTED CORE CONSTRUCTION:

16 PLAIT COVER CONSTRUCTION:

Halyards, Sheets, Control Lines, Kickers, Backstays, Out/Downhauls

Manufactured from high tenacity Polyester
Unaffected by water
Low creep
Zero shrinkage
Low water absorption
Manufactured from high tenacity Polyester
Good UV resistance
Good abrasion and heat resistance

Improved abrasion resistance Optimised pitch to yarn twist - improves strength and longevity

Firmer rounder rope, aids handling
Flexible product and easily handled
Protects load bearing core from dirt and abrasion

Round and firm construction

PROPERTIES

1.38 Exact figure varies with diameter **RELATIVE DENSITY:** Excellent resistance to most chemicals **CHEMICAL RESISTANCE:**

(additional information available on request)

UV RESISTANCE: MELTING POINT: CRITICAL TEMPERATURE:

Good 260°C N/A

TERMINATIONS


SPLICED EYE TERMINATION: N/A

ELONGATION

Typical working elongation (for a bedded in a rope):

@ 10% of break load: 1.7% @ 20% of break load: 2.8%

To break: 13.0%



PERFORMANCE

DIAMETER	CIRCUMFERENCE	MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN
2	3/32	2.7	0.18	110	242	1.1	99	218	1.0
3	1/8	6	0.40	202	444	2.0	182	400	1.8
4	5/32	10.7	0.72	377	829	3.7	339	746	3.3
5	3/16	21.5	1.44	702	1544	6.9	632	1390	6.2
6	7/32	26.8	1.80	986	2169	9.7	887	1952	8.7

Marlow Ropes Ltd Ropemaker Park Hailsham East Sussex, BN27 3GU England

Marlow Ropes, Inc. Cordage Business Park Plymouth MA 02360

www.marlowropes.com UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

