



MARINE PRODUCTS

Legendary Strength and Value.

EXCEEDS INDUSTRY SPECIFICATIONS
ENGINEERED IN CANADA
PROOF TESTED

titanmarineproducts.com

D766
G43
EMBOSSSED/FT



FINISH: HOT DIP GALVANIZED

PACKAGING: FULL DRUMS, CRATES

SPECS: EXCEEDS DIN 766

DIN766 G43 Windlass Chain uses a high tensile strength carbon steel, specifically designed for anchoring applications, that provides a greater strength-to-weight ratio than DIN766 G30. Hot dip galvanized short link chain is calibrated to latest DIN766 standard. Each link is calibrated to ensure proper fit for most metric windlasses. Check manufacturer's specification prior to purchase. Certificate available upon request.

TRADE SIZE mm	WIRE DIAMETER		INSIDE LENGTH		OUTSIDE WIDTH		WORKING LOAD LIMIT (WLL/SWL)		
	mm	in	mm	in	mm	in	kg	kN	lb
6	6	0.24	18.5	0.73	20.4	0.80	800	8.0	1800
7	7	0.28	22	0.83	23.8	0.94	1180	11.5	2600
8	8	0.31	24	0.94	27.2	1.07	1770	17.3	3900
10	10	0.39	28	1.10	36	1.42	2450	24.0	5400
10	10	0.39	30	1.18	35	1.38	2450	24.0	5400
11	11	0.43	31	1.22	40	1.57	2680	26.7	5900
12	12	0.47	36	1.42	41	1.61	3270	32.0	7200