

H-Series

The stylish, horizontal H-Series Windlasses use the reliable worm gearbox technology. The integral contactor simplifies wiring and is protected by a durable maincase. The unit's waterproof seal requires minimum maintenance, and since you can install it in one piece, getting started is quick and easy.

- Quick, easy, one-piece installation
- Stainless steel warping drum and unique W.A.R.P. (Wear and Abrasion Reduction Pattern) finish
- Robust horizontal worm motor-gearbox for reliable performance
- Integral contactor protected by maincase
- Sealed waterproof unit requires minimum maintenance
- Aluminium and composite maincase for reduced weight
- For boats up to 14m (48ft)



H2 & H3 Specifications

PART NUMBER	PART NUMBER	MODEL	MOTOR SUPPLY Voltage	GYPSY NO.	MOTOR POWER Watt	MAXIMUM PULL		MAXIMUM LINE SPEED		WORKING LOAD LIMIT		NORMAL CURRENT DRAW Amp	NORMAL LINE SPEED		WEIGHT GYPSY ONLY		WEIGHT GYPSY/DRUM		CIRCUIT BREAKER Amp
						kg	lb	m/min	ft/min	kg	lb		m	ft	kg	lb	kg	lb	
69600533	69600537	H2	12	505	700	650	1433	21	69	163	358	80	17	56	21.5	47	23.5	52	90
69600534	69600538	H2	12	506	700	650	1433	21	69	163	358	80	17	56	21.5	47	23.5	52	90
	69600545	H3	12	505	1000	890	1962	28	92	215	475	85	18	59	23.5	52	25.5	56	110
69600542	69600546	H3	12	506	1000	890	1962	28	92	215	475	85	18	59	23.5	52	25.5	56	110
	69600548	H3	24	506	1000	1020	2248	30	98	243	535	60	20	66	23.5	52	25.5	56	90

Kits include: Built-in-dual-direction contactor, breaker and rocker switch

H2 & H3 Gypsy Specifications

GYPSY NUMBER	SIZE mm	CHAIN DESCRIPTION	ROPE DESCRIPTION	
			mm	in
505	8	5/16" BB, 5/16" ISO G4, 8mm DIN 766, 8mm ISO 4565	14-16	9/16-5/8
506	10	3/8" BBB, 10mm DIN 766, Lewmar 9.5 G40	14-16	9/16-5/8



Manual Recovery Kit

Available on the H2/H3 as an optional extra, it remains fitted to the unit for user convenience

PART NO.	DESCRIPTION
66840045	M/R Kit H2/H3

Dimensions Diagram

